

Ball / Land Grid Array Sockets Clamshell Type




E-tec is now the leading BGA socket manufacturer.

EP patents 0829188, 0897655 US patents 6190181, 6249440 Patented in other countries.

Clamshell sockets are available for any chip size and grid pattern. They are available in SMT, thru-hole and solderless compression type versions. The SMT socket is simply placed and reflowed onto the PCB in the same way as the chip and it only requires a small amount of additional board space. A lever is added to the Quick lock retention cover if the pincount exceeds 81 pins which allows the required pressdown forces to be applied easily.

We aim to solve your requirements - many different terminals and configurations are available. Your custom sets our standards!



Please note, we will always request the chip data to ensure we offer a compatible socket.

SMT style

optional locating peg

PCB Pad Layout

Pitch

solder pad

- Ø 0,60mm/.024" if pitch 1,27mm
- Ø 0,50mm/.020" if pitch 1,00mm
- Ø 0,40mm/.016" if pitch 0,80mm
- Ø 0,35mm/.014" if pitch 0,75mm
- Ø 0,35mm/.014" if pitch 0,65mm
- Ø 0,30mm/.012" if pitch 0,50mm

Soldertail style

Soldertail Ø

PCB Hole Layout

Pitch

solder hole

Soldertail dimension:

- Ø 0,42mm/.016" if pitch 1,27mm
- Ø 0,29mm/.011" if pitch 1,00mm
- Ø 0,29mm/.011" if pitch 0,80mm
- Ø 0,27mm/.010" if pitch 0,75mm
- Ø 0,27mm/.010" if pitch 0,65mm
- Ø 0,27mm/.010" if pitch 0,50mm
- Ø 0,17mm/.007" if pitch 0,40mm

PCB solder hole:

- Ø 0,60mm/.024" if pitch 1,27mm
- Ø 0,50mm/.020" if pitch 1,00mm
- Ø 0,40mm/.016" if pitch 0,80mm
- Ø 0,35mm/.014" if pitch 0,75mm
- Ø 0,35mm/.014" if pitch 0,65mm
- Ø 0,25mm/.010" if pitch 0,40mm

Solderless Compression style

Retention Cover

BGA Chip

BGA socket body

PCB

Assembly Board

mounting screw

PCB Pad Layout

Pitch

Solder Pad

You may request any specific socket dimension from info@e-tec.com

- gold plated pads Ø 0,70mm/.027" if pitch 1,27mm
- gold plated pads Ø 0,60mm/.024" if pitch 1,00mm
- gold plated pads Ø 0,50mm/.020" if pitch 0,80mm
- gold plated pads Ø 0,45mm/.018" if pitch 0,75mm
- gold plated pads Ø 0,40mm/.016" if pitch 0,65mm
- gold plated pads Ø 0,35mm/.012" if pitch 0,50mm
- gold plated pads Ø 0,25mm/.010" if pitch 0,40mm

Important Note:

Please check the ball diameters & heights of your chip prior to ordering the standard E-tec BGA (BPC, BCC) sockets. Any deviation has to be communicated to E-tec in order to check compatibility with the standard socket design and if necessary to obtain a special order code adapted to your chip dimensions. The standard solderball diameters & heights are the following:

Pitch	ball diameters min/max	ball height min/max
0.50mm	0.25mm / 0.35mm	0.15mm / 0.30mm
0.65mm	0.25mm / 0.45mm	0.15mm / 0.30mm
0.75mm	0.25mm / 0.45mm	0.15mm / 0.40mm
0.80mm	0.40mm / 0.55mm	0.25mm / 0.45mm
1.00mm	0.50mm / 0.70mm	0.30mm / 0.50mm

1.27mm & 1.50mm

- a) plastic chips (BPC) 0.60mm / 1.00mm 0.50mm / 0.70mm
- b) ceramic chips (BCC) 0.60mm / 1.00mm 0.80mm / 1.00mm

If the minimum ball diameter of a given chip falls below the above indications, then a BUC socket will generally be proposed.

Specifications

Mechanical data	
Contact life	10.000 cycles min.
Retention System life	10.000 cycles min.
Solderability	as per IEC 60068-2-58
Individual contact force	40 grams max.
Material	
Insulator (RoHS compliant)	High temp plastic or epoxy FR4
Terminal (RoHS compliant)	Brass
Contact (RoHS compliant)	BeCu
Electrical data	
Contact resistance	< 100 mΩ
Current rating	500 mA max.
Insulation resistance at 500V DC	100 MΩ if 0.50 to 0.80mm pitch 500 MΩ 1.00mm pitch upwards
Breakdown voltage at 60 Hz	500V min.
Capacitance	< 1 pF
Inductance	< 2 nH
Operating temperature	-55°C to +125°C ; 260°C for 60 sec.

Recommendations:

Solder paste: Please use a solder paste w/o any silver!
Solder profile: Please refer to our website www.e-tec.com

E-tec solderless sockets are adapted to a standard PCB thickness of 1.60mm. For a different PCB thickness, please inform E-tec first!

How to order

X X C x x x x - x x x x - x x X X x x L ← optional for locating pegs

Device Type

- B** = Ball Grid
- L** = Land Grid
- C** = Column Grid

Device Material

- C** = std. socket for ceramic device
- P** = std. socket for plastic device
- U** = socket adapted to small diameter solderballs

Pitch

- 04** = 0,40mm
- 05** = 0,50mm
- 06** = 0,65mm
- 07** = 0,75mm
- 08** = 0,80mm
- 10** = 1,00mm
- 12** = 1,27mm
- 15** = 1,50mm
- others on request

Grid Code

will be given by the factory after receipt of the chip datasheet

Config Code

Plating

- 95** = tin/gold (tin leadfree)
- 55** = gold only for solderless Compression Type

Nbr of contacts

depends on ballcount of chip

Contact Type

- 30** = standard SMT... („A“ = 1,20mm if 1,27mm pitch; 0,80mm if 1,00mm pitch, 0,60 if 0,80mm pitch; 0,40mm if <0.80mm pitch)
- 29** = raised SMT... („A“ = 5,00mm if 1,27mm pitch; 3,20mm if 1,00mm pitch; 2,80mm if 0,80mm pitch, 2,30mm if <0.80mm pitch)
- 28** = special raised SMT - only for 1.00 & 0.80mm pitch..... („A“ = 4,50mm)
- 70** = standard solder tail..... („A“ = 3.30 if 1.27mm pitch, 2.80 if 1.00mm or 0.80mm pitch, 2,30mm if <0.80mm pitch)
- 90** = solderless Compression Type