



- Lexan Window-door:** L -160 mm H -150 mm

- Box body:** L -58 mm H -58 mm

- Useful Depth:** P -40 mm

- Opening angle (external door):** 180°

- Nr of modular switchgears per row as in the schedule**

Order code	Model	Modular switchgears / Rows		External dimensions mm			kg	m ³
				L	H	P		
013180410	AMPV 4240	12	2	420	400	105	4	0,01
013180420	AMPV 4264	12	4	420	600	105	5	0,01
013180430	AMPV 5240	18	2	520	400	105	5	0,01
013180440	AMPV 5250	18	3	520	500	105	5	0,01
013180450	AMPV 5260	18	4	520	600	105	4	0,01
013180460	AMPV 3545	2 Sockets		350	450	125	7	0,03
013180470	AMPV 3565	3 Sockets		350	650	125	8	0,03

N.B.: when you order, please specify the hinging side.

All data can undergo changes without notice.

AMPV



Internal mounting plate on request

Standard operating

AMPV with flush solid door, pressure opening door, preset for modular switchgears and with cable inlet holes.

Category of protection and certification	IP44 IK10	EN 60 529/09.2000 EN 50 102/05.96
	CE	EN 62208 : 2003 89/392/EEC
Thickness	Box body 2,5 mm FeZn Frame 1,2 mm	
Material	AISI 304 Wnr. 1.4301 brushed fine scotch brite medium	
on request	Manufacturing in AISI 316 Wnr. 1.4404 Internal mounting plate	

AISI 304 stainless steel flush mounting boxes with frame to be fixed on the wall, preset for modular switchgears, sockets with block switch, hydraulic connections and for noble gases. They are particularly fit for the hygiene field, big plants and public buildings in general. Door and frame are welded together to have a whole structure to be screwed to the FeZn body inside the wall. The enclosure body is equipped with supports for DIN rail and cable inlet holes.