

Useful Depth:	P -52÷-64 mm
Lexan Window-door:	L -125 mm H -125 mm
Door opening:	120°
DIN rail adjustment:	95 mm
Height terminal box covering panel:	H1 = H- (Nr switchgears for 150 mm) -75 mm

Nr of modular switchgears for row as in the schedule

Order code	Model	Mo-dular	Switch-gears	Ext. dim. mm			kg	m ³
				L	H	P		
013170030	EKMV 25 35 21	12	2	250	350	210	10,0	0,03
013170050	EKMV 30 30 21	16	2	300	300	210	9,0	0,03
013170070	EKMV 30 45 21	16	2	300	450	210	13,0	0,04
013170090	EKMV 35 40 21	24	2	350	400	210	13,5	0,04
013170130	EKMV 40 35 21	32	2	400	350	210	13,5	0,04
013170150	EKMV 40 50 25	32	2+1*	400	500	250	14,5	0,06
013170175	EKMV 45 45 21	36	2	450	450	210	13,5	0,05
013170185	EKMV 45 45 25	36	2	450	450	250	16,0	0,08
013170190	EKMV 45 60 25	36	2+1*	450	600	250	22,0	0,10

Order code	Model	Mo-dular	Switch-gears	Ext. dim. mm			kg	m ³
				L	H	P		
013170210	EKMV 50 70 25	60	3+1*	500	700	250	28,0	0,16
013170230	EKMV 60 60 25	48	2+1*	600	600	250	28,0	0,14
013170250	EKMV 60 75 25	72	3+1*	600	750	250	30,0	0,17
013170270	EKMV 60 90 30	96	4+1*	600	900	300	41,0	0,23
013170290	EKMV 60 120 30	144	6+1*	600	1200	300	54,0	0,30
013170310	EKMV 75 60 25	72	2+1*	750	600	250	33,0	0,17
013170330	EKMV 75 100 30	180	5+1*	750	1000	300	54,0	0,31
013170350	EKMV 80 120 30	228	6+1*	800	1200	300	66,0	0,39

+1* Identifies the stainless steel panel covering the terminal box.

All data can undergo changes without notice.

EKMV



Wall fixing brackets
P. 82



Support for DIN rail
P. 82






Rain canopy
P. 87



Standard operating

EKMV with Lexan door, stainless steel screwed covering panels, adjustable supports for Din rail, without internal moulding plate. They are provided with fastenings for M6 screws (threaded nuts).

Category of protection and certification	 IP66 IK10	EN 60 529/09.2000 EN 50 102/05.96
	 TYPE 4x 12, 1, 4 NEMA 4x 12, 1, 4	Standard 508 Standard 250
	 EN 62208 : 2003	89/392/EEC
Thickness	According to external dimensions 1,2 / 1,5 mm	
Material	AISI 304 Wnr. 1.4301 brushed fine scotch brite medium	
on request	Internal mounting plate Manufacturing in AISI 316 Wnr. 1.4404 Hinged covering panels Stratified glass 3+3 door	

AISI 304 stainless steel enclosures, ready for modular switchgears. The distance from the Lexan door and the internal screwed stainless steel covers (H=150mm) with slits for modular switchgears and support for DIN rail is adjustable between 52 and 64 mm. The back is equipped with fastenings for M6 screws (threaded nuts).