

Internal mounting plate: L -55 mm H -55 mm

Lexan Window-door: L -115 mm H -110 mm

Useful Depth: P -20 mm

Door opening: 145°

Order code	Model	Nr. Door	Ext. dim. mm			kg	m ³
			L	H	P		
013120555	EKV 20 30 15	1	200	300	155	7,0	0,02
013120565	EKV 25 35 21	1	250	350	210	8,0	0,04
013120575	EKV 30 30 21	1	300	300	210	8,0	0,04
013120585	EKV 30 38 21	1	300	380	210	9,0	0,04
013120595	EKV 30 45 21	1	300	450	210	11,0	0,05
013120605	EKV 35 40 21	1	350	400	210	11,0	0,05
013120625	EKV 38 38 21	1	380	380	210	12,0	0,05
013120635	EKV 38 60 21	1	380	600	210	19,0	0,08
013120645	EKV 40 35 21	1	400	350	210	11,0	0,05
013120665	EKV 45 45 21	1	450	450	210	15,0	0,07
013120615	EKV 45 45 25	1	450	450	250	17,0	0,08
013120675	EKV 45 45 30	1	450	450	300	19,0	0,10
013120655	EKV 40 50 25	1	400	500	250	15,0	0,08
013120685	EKV 45 60 25	1	450	600	250	21,0	0,11
013120695	EKV 45 60 30	1	450	600	300	23,0	0,12
013120705	EKV 45 60 40	1	450	600	400	26,0	0,16
013120715	EKV 50 50 21	1	500	500	210	19,0	0,09
013120725	EKV 50 50 30	1	500	500	300	20,0	0,12
013120735	EKV 50 70 25	1	500	700	250	28,0	0,14
013120755	EKV 60 45 25	1	600	450	250	21,0	0,11

Order code	Model	Nr. Door	Ext. dim. mm			kg	m ³
			L	H	P		
013120765	EKV 60 60 21	1	600	600	210	24,0	0,12
013120775	EKV 60 60 25	1	600	600	250	27,0	0,14
013120785	EKV 60 60 40	1	600	600	400	36,0	0,21
013120795	EKV 60 75 25	1	600	750	250	33,0	0,17
013120805	EKV 60 75 30	1	600	750	300	35,0	0,20
013120815	EKV 60 75 40	1	600	750	400	43,0	0,25
013120835	EKV 60 90 30	1	600	900	300	43,0	0,23
013120845	EKV 60 90 40	1	600	900	400	45,0	0,30
013120855	EKV 60 120 30	1	600	1200	300	54,0	0,30
013120865	EKV 60 120 40	1	600	1200	400	67,0	0,39
013120875	EKV 70 50 25	1	700	500	250	27,0	0,14
013120885	EKV 75 60 25	1	750	600	250	33,0	0,17
013120895	EKV 75 100 30	1	750	1000	300	45,0	0,31
013120905	EKV 76 76 30	1	760	760	300	40,0	0,25
013120915	EKV 80 100 30	1	800	1000	300	53,0	0,33
013120925	EKV 80 120 30	1	800	1200	300	71,0	0,40
013120935	EKV 90 60 30	1	900	600	300	43,0	0,24
013120945	EKV 100 75 30	1	1000	750	300	45,0	0,32
013120955	EKV 100 100 30	1	1000	1000	300	76,0	0,41
013120965	EKV 100 120 30	1	1000	1200	300	81,0	0,49



Wall fixing brackets
P. 82



Rain canopy
P. 87






Ventilation kit IP55
P. 117



Standard operating

EKV with hinged Lexan door, internal mounting plate. They're provided with fastenings for M6 screws (threaded nuts).

Category of protection and certification	 IP66 IK10	EN 60 529/09.2000 EN 50 102/05.96
	 TYPE 4x 12, 1, 4 NEMA 4x 12, 1, 4	Standard 508 Standard 250
	 EN 62208 : 2003	89/392/EEC
Thickness	According to external dimensions 1,2 / 1,5 mm	
Material	AISI 304 Wnr. 1.4301 brushed fine scotch brite medium	
Internal mounting plate	2,5 mm FeZn	
on request	Manufacturing in AISI 316 Wnr. 1.4404 Stratified glass 3+3 door	

AISI 304 stainless steel enclosures with Lexan door, can be fixed on machineries or walls. They are provided with back threaded nuts with M6 screws. Models starting from W=1200 mm are equipped with two overlapping doors L=600 mm, without central post.