

Switchcraft®

EH Series CAT5e & CAT6

CAT5e Unshielded



CAT5e Shielded



CAT6 Unshielded



CAT6 Shielded



EH Series CAT5e & CAT6

Switchcraft® introduces the newest additions to our line of EH Series panel mount connectors...

CAT5e and CAT6 feedthru's are available shielded and unshielded. Shielded versions provide EMI protection and high noise immunity.

All EH Series CAT5e and CAT6 connectors comply with TIA/EIA 568B standards.

Built by hand in Chicago, USA 

Part Numbers:

	Shielded	Unshielded
CAT5e	EHRJ45P5ES	EHRJ45P5E
CAT6	EHRJ45P6S	EHRJ45P6

Specifications:

Electrical:

- TIA/EIA Rating: CAT5e / CAT6
- Frequency Bandwidth: CAT5e (1-100 MHz)
- Frequency Bandwidth: CAT6 (1-250 MHz)
- Number of Contacts: 8
- Rated Current: 1.5 Amps
- Insulation Resistance: 500 MΩ
- Dielectric Strength: 1 kVac
- Contact Resistance: < 20 mΩ

Mechanical:

- Insertion Life: >750 mating cycles
- Operating Temperature: -10°C to +60°C
- Storage Temperature: -40°C to +70°C

Material:

- Mounting Adapter: UL94HB Thermoplastic
- Coupler: UL94V-0 Thermoplastic
- Contacts: Copper Alloy
- Contact Plating: Au (50μ" over Ni plating)

RoHS Compliant.

Switchcraft®

www.switchcraft.com
5555 N. Elston Avenue/Chicago, IL 60630
Phone: 773-792-2700 Fax: 773-792-2129

Addendum to New Product Bulletin #560B

